

CAPACITIES: VALENT VPR SERIES

	Nominal airflow (cfm)														
	550	650	1,000	1,500	2,000	3,000	4,000	5,000	6,000	8,000	10,000	12,000	14,000	16,000	18,000
AIRFLOW CAPACITIES VPR/VPRX	V10 (VPR only)														
	110														
	210														
	310														
	352														
VPRE	110														
	210														
	310														
	352														
VPRP	110														
	210														
	310														
	352														
VPRC	110														
	210														
	310														
	352														

Airflow ranges are shown with packaged air cooled DX refrigeration and do not take into account actual design loads.

	Nominal tonnage																
	4	5	6	7	8	10	13	16	18	20	25	30	35	40	50	60	70
REFRIGERATION CAPACITIES Packaged air cooled	V10																
	110																
	210																
	310																
	352																
Split air cooled	110																
	210																
	310																
Water source heat pump	110																
	210																
	310																
Air source heat pump	110																
	210																

	Input capacity (MBh)													
	75	100	150	200	250	300	400	500	600	700	800	1,000	1,200	
HEATING CAPACITIES Indirect gas, temperator	V10 (indirect gas only)													
	110													
	210													
	310													
	352 (indirect gas only)													
	Electric capacity (kW)													
	10	15	20	30	40	50	60	80	90	100	125	150	175	200
SCR electric	110													
	210													
	310													
	352													

Electric heat sizes shown do not account for unit voltage.